

DART SERVICE INSTRUCTION




**TO AMEND INSTALLATION INSTRUCTIONS D206-642 REV. N
AND INSTRUCTIONS FOR CONTINUED AIRWORTHINESS ICA-D206-642 REV. 3**

REF FAA STC SA00475SE

REF TCCA STC SH98-4

REF EASA STC EASA.IM.R.S.01320

The D206-642-111/-112/-113/-114 skidtubes, which can replace 206-320-201/-202/-203/-204 skidtubes, are approved for installation on the 206-320-121 (FWD) and 206-320-122/-126 (AFT) crosstubes, which are approved replacements for 206-050-286-101 (FWD) and 206-050-286-105 (AFT) crosstubes per AAI STC SH2764SO-D.

A	NEW ISSUE	RF	10.04.19
REV.	DESCRIPTION	BY	DATE
DESIGN	DS	DART AEROSPACE USA, INC.	
DRAWN	RF	PORT HADLOCK, WA	
CHECKED		DRAWING NO.	REV. A
MFG. APPR.	N/A	DSI 9516	SHEET 1 OF 1
APPROVED		TITLE	SCALE
DE APPR.		SKIDTUBES COMPATIBILITY	NTS
DATE	10.04.19	COPYRIGHT © 2010 BY DART AEROSPACE USA, INC. THIS DOCUMENT IS PRIVATE AND CONFIDENTIAL AND IS SUPPLIED ON THE EXPRESS CONDITION THAT IT IS NOT TO BE USED FOR ANY PURPOSE OR COPIED OR COMMUNICATED TO ANY OTHER PERSON WITHOUT WRITTEN PERMISSION FROM DART AEROSPACE USA, INC.	